


WAAS CH 66038 W30A	APP CRS 306°	Rwy Ldg TDZE Apt Elev	4200 2754 2756
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 30

BEACH (20U)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Rwy 30 helicopter visibility reduction below ¾ SM NA.		MISSED APPROACH: Climb to 4700 direct EKENE and hold.
AWOS-3 118.175	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF) 0



ELEV 2756		TDZE 2754		4700	EKENE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 27).		5 NM Holding Pattern
MIRL Rwy 12-30 0		* LNAV only		RW30		DEKRE 2.2 NM to RW30		EKOYU
4200 X 60		* 1.3 NM to RW30		* 3480		CAXET 4400		126° → 6000
306°		1.3 NM		0.9 NM		2.9 NM		← 306° 5000
								GP 3.00° TCH 40
CATEGORY		A		B		C		D
LPV DA		3004-1		250 (300-1)		NA		
LNAV/VNAV DA		3175-1½		421 (500-1½)		NA		
LNAV MDA		3180-1		426 (500-1)		NA		
CIRCLING		3280-1 524 (600-1)		3360-1 604 (700-1)		NA		

NC-1, 09 JUL 2026 to 06 AUG 2026

NC-1, 09 JUL 2026 to 06 AUG 2026