

WAAS CH 82718 W04A	APP CRS 038°	Rwy Ldg 13502 TDZE 3607 Apt Elev 3607
--	------------------------	--

RNAV (GPS) Y RWY 4

RICK HUSBAND AMARILLO INTL (AMA)


RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -22°C or above 41°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, and LNAV/VNAV and LNAV Cat E to 1¼ SM.
** RVR 1800 authorized with use of FD or AP or HUD to DA.


MALSR

MISSED APPROACH: Climb to 5400 direct CIPLI and on track 053° to ZUKTA and hold.

ATIS 118.85 350.3	AMARILLO APP CON* 119.5 307.0	AMARILLO TOWER* 118.3 (CTAF) 257.9	GND CON 121.9 348.6	CLNC DEL 121.65 239.275	UNICOM 122.95
-----------------------------	---	--	-------------------------------	-----------------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 61).					5400 ↑	CIRPL ✦	tr 053°	ZUKTA ✦
MOZFO					JOPNI	WEKOB 1.9 NM to RW04	*1.1 NM to RW04	*LNAV only.
5300					5200	5200	*4240	RW04
GP 3.00° TCH 44					6 NM	2.9 NM	0.8 NM	1.1 NM
CATEGORY		A	B	C	D	E		
LPV DA **			3807/24	200 (200-½)				
LNAV/ VNAV			4028/50	421 (500-1)				
LNAV MDA		4040/24	433 (500-½)	4040/40 433 (500-¾)	4040/50	433 (500-1)		
CIRCLING		4080-1	473 (500-1)	4240-1¾ 633 (700-1¾)	4280-2¼ 673 (700-2¼)	4460-3 853 (900-3)		



SC-2, 06 AUG 2026 to 03 SEP 2026

SC-2, 06 AUG 2026 to 03 SEP 2026