

APP CRS
003°

Rwy Ldg **10000**
TDZE **707**
Apt Elev **748**

RNAV (RNP) Z RWY 1R
CHARLOTTE/DOUGLAS INTL (CLT)

RNP AR APCH - GPS.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, procedure NA below -7°C or above 54°C. For inop ALS, increase RNP 0.30 visibility all Cats to 1 1/2 SM.

ALSF-2

MISSED APPROACH: Climb to 3000 on track 003° to TOMME and hold.

D-ATIS	CHARLOTTE APP CON		CHARLOTTE TOWER		GND CON
121.15	128.325 (001°-119°)	257.2 (180°-359°)	118.1 257.8 (18L-36R)		121.8 348.6 (W)
	120.05 (120°-295°)	307.8 (360°-179°)	126.4 257.8 (1R-19L)		121.9 348.6 (E)
	134.75 (296°-360°)		133.35 257.8 (1L-19R)		

ELEV 748

D

TDZE 707

HIRL all Rwys

REIL Rwy 18L

TDZL/RCLS Rwys 1L, 1R, 19R, 36R

3000	tr 003°	TOMME	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).				SOLMN
			GLASI	NIVSE	MARJO	HUNEX	8000
			2500	3000	4000	5000	
			5.5 NM	1.7 NM	3.1 NM	3 NM	
			A		B	C	D
			RNP 0.11 DA	1134/40	427 (400-3/4)		
			RNP 0.30 DA	1180/50	473 (500-1)		
AUTHORIZATION REQUIRED							

CHARLOTTE, NORTH CAROLINA

Orig 09JUL26

35°13'N-80°57'W

CHARLOTTE/DOUGLAS INTL (CLT)

RNAV (RNP) Z RWY 1R