



LOC I-ATD	APP CRS	Rwy Ldg	10900
108.9	061°	TDZE	998
		Apt Elev	1009

ILS or LOC RWY 6L

JAMES M COX DAYTON INTL (DAY)

▼ ▲ Simultaneous approach authorized. For inop ALSF-2, increase S-LOC 6L Cat C/D visibility to 1½ mile. ALSF-2 Ⓐ MISSED APPROACH: Climb to 2000 then climbing left turn to 3000 direct DQN VOR/DME and hold.	ATIS 125.8 COLUMBUS APP CON 118.85 305.2 (091°-180°) 134.45 323.15 (181°-090°) DAYTON TOWER 119.9 257.7 GND CON 121.9
---	--



CATEGORY	A	B	C	D
S-ILS 6L	1198/18 200 (200-½)			
S-LOC 6L	1460/24	462 (500-½)	1460/50	462 (500-1)
CIRCLING	1580-1	571 (600-1)	1580-1½ 571 (600-1½)	1640-2 631 (700-2)
LEBNE FIX MINIMUMS (DUAL VOR RECEIVERS REQUIRED)				
S-LOC 6L	1380/24	382 (400-½)	1380/35	382 (400-¾)
CIRCLING	1580-1	571 (600-1)	1580-1½ 571 (600-1½)	1640-2 631 (700-2)

