

WAAS CH 40006 W18A	APP CRS 176°	Rwy Ldg TDZE Apt Elev	9001 900 901
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 18
HECTOR INTL (FAR)

RNP APCH.

▼



▲

For inoperative MALS, increase LPV Cat E visibility to RVR 4000 and LNAV/VNAV Cat E and LNAV Cat D and E to RVR 6000. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F).
#RVR 1800 authorized with use of FD or AP or HUD to DA.


MALS

MISSED APPROACH:
Climb to 3500 direct
KOBME and hold.

ATIS 124.5 379.2	FARGO APP CON 120.4 377.15	FARGO TOWER 133.8 290.4	GND CON 121.9 348.6
----------------------------	--------------------------------------	-----------------------------------	-------------------------------



CATEGORY	A	B	C	D	E
LPV DA#	1100/24	200 (200-½)			
LNAV/VNAV DA	1272/40	372 (400-¾)			
LNAV MDA	1260/24	360 (400-½)	1260/50	360 (400-1)	
CIRCLING	1380-1	479 (500-1)	1520-1¾ 619 (700-1¾)	1620-2¼ 719 (800-2¼)	1620-2½ 719 (700-2½)



NC-1, 06 AUG 2026 to 03 SEP 2026

NC-1, 06 AUG 2026 to 03 SEP 2026