

LOC/DME I-BYW 110.9 Chan 46	APP CRS 091°	Rwy Ldg TDZE 7500 680 Apt Elev 680	ILS PRM Y RWY 10R (CLOSE PARALLEL) CHICAGO O'HARE INTL (ORD)
---	------------------------	--	---

RNAV 1-GPS or RADAR required for procedure entry. DME or RADAR required.
From GIBNS: RNAV-1 GPS required.

Simultaneous approach authorized. Use of FD or AP required during simultaneous operations. Dual VHF Comm required.
See additional requirements on AAUP.

ALSIF-2

MISSED APPROACH: Climb to 1200 then climbing right turn to 4000 direct DPA VOR/DME and hold.

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 133.0 348.0 PRM 128.05	GND CON (TWR CENTER) 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS) 121.75 (OBND) 121.9 (IBND)
--------------------------------	---	---	---

MSA ORD 25 NM
3400

FERLL I-BYW [27.8] RADAR
MLESEN I-BYW [24.7] RADAR
OLLGA I-BYW [21.5] RADAR
LEATH I-BYW [18.4] RADAR
GOOZY I-BYW [15.3] RADAR
KVENN I-BYW [12.1] RADAR
FLYN INT I-BYW [6.6] RADAR

091°
8000 (3.1)
7000 (3.1)
6000 (3.1)
5000 (3.1)
4000 (3.1)
2300 (5.6)

DUPAGE
114.55 DPA
Chan 92(Y)

LOCALIZER 110.9
I-BYW
Chan 46
LOC offset 2.50°

ALTERNATE MISSED
APCH FIX
JOLIET
112.3
Chan 70

1200 4000 DPA

113.0 Obk Chan 77
R-195

FERLL I-BYW [27.8] RADAR
MLESEN I-BYW [24.7] RADAR
OLLGA I-BYW [21.5] RADAR
LEATH I-BYW [18.4] RADAR
GOOZY I-BYW [15.3] RADAR
KVENN I-BYW [12.1] RADAR
FLYN INT I-BYW [6.6] RADAR

091°
9000
8000
7000
6000
5000
4000
2300

GS 3.00°
TCH 55

3.1 NM 3.1 NM 3.1 NM 3.1 NM 3.1 NM 5.6 NM 4.9 NM

CATEGORY A B C D

S-ILS 10R 930/24 250 (300-1/2)

1200 4000 DPA

091°

HIRL all rwys
TDZL/RCLS all rwys except 4L

CHICAGO, ILLINOIS
Orig-D 22APR21

41°59'N-87°54'W

CHICAGO O'HARE INTL (ORD)
ILS PRM Y RWY 10R (CLOSE PARALLEL)