

WAAS CH 48904 W10A	APP CRS 093°	Rwy Ldg 12246 TDZE 672 Apt Elev 680
--	------------------------	--

RNAV (GPS) RWY 10L

CHICAGO O'HARE INTL (ORD)

RADAR required for procedure entry: RNP APCH.


▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSIF-2

MISSED APPROACH: Climb to 4000 direct XURXU and on track 161° to CGT VORTAC and hold.

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 132.7 348.0	GND CON (TWR CENTER) 124.125 (TWR NORTH) 121.75 (OBND) 118.05 (TWR SOUTH) 121.9 (IBND) 226.675 (ALL TWS)
--------------------------------	---	------------------------------------	--



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 74).

4000

XURXU

tr 161°

CGT

* LNAV only.

GP 3.00° TCH 56

ARIST 9000 092°

KALZO 8000 093°

BURKE 7000

SYSCO 6000

PRATT 5000

CARLE 4000

ANACO 2.7 NM to RWY10L

BUGSE 2300

* 1.2 NM to RWY10L

RWY10L

2300 *1580

CATEGORY	A	B	C	D
LPV DA	872/18		200 (200-½)	
LNAV/VNAV DA	1062/35		390 (400-¾)	
LNAV MDA	1120/24	448 (500-½)	1120/45	448 (500-¾)

HIRL all rwyys
TDZL/RCLS all rwyys except 4L