

WAAS CH 70643 W27D	APP CRS 273°	Rwy Ldg 11245 TDZE 653 Apt Elev 680
--	------------------------	--

RNAV (GPS) RWY 27C

CHICAGO O'HARE INTL (ORD)



RNP APCH.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to RVR 6000.

ALSF-2

MISSED APPROACH:
Climb to 1100 then climbing right turn to 4000 direct UKUNE and hold.

D-ATIS 135.4 282.225	CHICAGO APP CON 119.0 292.125	O'HARE TOWER 121.15 348.0	GND CON 124.125 (TWR NORTH) 118.05 (TWR SOUTH) 226.675 (ALL TWRS)	(TWR CENTER) 121.75 (OBND) 121.9 (IBND)
--------------------------------	---	-------------------------------------	---	---



1100	4000	UKUNE	VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 75).		NCHLS
*LNAV only.		DRISCL	JMBBO	MRRFF	BOOWW
YVONE 1.4 NM to RWY 27C		2200	4000	5000	7000
RWY 27C		1160*	2200	273°	8000
1.4		3.3 NM	→ 6 NM →	3.1 NM	3.1 NM
CATEGORY	A	B	C	D	
LPV	DA	853/18		200 (200-½)	
LNAV/VNAV	DA	1086/40		433 (500-¾)	
LNAV MDA	1060/24		407 (400-½)		1060/40 407 (400-¾)