

HI-ILS Y or LOC Y RWY 35L

LOC I-EFD 111.1 APCH CRS 354° Rwy Idg 9001 TDZE 28 Arprt Elev 33 [USAF] ELLINGTON (KEFD)

DME required. RADAR required for procedure entry.

When ALS inop, increase CAT CDE RVR to 60.
Circling not authorized W of rwy 17L-35R

MALSF MISSED APPROACH: Climb to 500 then climbing right turn to 3100 via EFD TACAN R-136 to WATFO/EFD 16 DME and hold.

ATIS 135.575 269.9	HOUSTON APP CON 134.45 284.0	TOWER 126.05 253.5	GND CON 121.6 275.8
-----------------------	---------------------------------	-----------------------	------------------------

EFD TACAN N29°36.36' W95°09.58'
CANDI N29°39.24' W95°18.17'
DROPP N29°13.63' W95°32.07'
WATFO N29°23.90' W94°58.07'

LOCALIZER 111.1 I-EFD

TRINITY 114.75 MHF Chan 94(Y)

EMERG SAFE ALT 100 NM 16,000

500	3100	WATFO EFD 16	MARZY EFD 7	PAHSU EFD 15	KOREJ EFD 18
-----	------	--------------	-------------	--------------	--------------

CATEGORY	C	D	E
S-ILS 35L	228/40	200	(200-34)
S-LOC 35L *	440/50	412	(500-1)
** CIRCLING	580-1½ 547 (600-1½)	640-2 607 (700-2)	700-2½ 667 (700-2½)

HI-ILS Y or LOC Y RWY 35L

SC-5, 06 AUG 2026 to 03 SEP 2026

SC-5, 06 AUG 2026 to 03 SEP 2026