

APP CRS 320°	Rwy Ldg	7278
	TDZE	793
	Apt Elev	796

RNAV (RNP) Z RWY 32

INDIANAPOLIS INTL (IND)

▼

For uncompensated Baro-VNAV systems, procedure NA below -18°C (2°F) or above 54°C (130°F). GPS required.

MALSR

MISSED APPROACH: Climb to 3000 on track 320° to KEADY and hold.

D-ATIS 134.25	INDIANAPOLIS APP CON 128.175 317.8	INDY TOWER 120.9 251.1	GND CON 121.9	CLNC DEL 128.75 251.1	CPDLC
-------------------------	--	----------------------------------	-------------------------	---------------------------------	-------

The main chart displays the RNP Z RWY 32 procedure. Key features include:

- Initial Approach:** (IF) CRCL 6000 210K (RF REQD) at 4400 ft, (IF) HNKLE 5000 210K (RF REQD) at 3600 ft, and (IF) PNFLD 6000 210K (RF REQD) at 4400 ft.
- Intermediate Approach:** (FAF) BTTLR at 2400 ft, CUREG 200K at 2400 ft, and EVAVE 200K at 3600 ft.
- Final Approach:** RWY 32 at 796 ft, with a missed approach fix at KEADY (4 NM, 139°).
- Obstacles:** HIKEK (3600 ft), BDAWG 5000 (RF REQD), and OZMOE 4500 210K.
- Navigation Aids:** MSA RWY 32 25 NM (3100 ft), TWR, and various VORTAC stations.

ELEV 796 **D** TDZE 793

3000

↑

Ir 320°

KEADY

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 73).

BTTLR

2400

GP 3.00°

TCH 53

See planview for multiple IF locations.

4.9 NM

CATEGORY	A	B	C	D
RNP 0.19 DA		1134/30	341 (400-%)	
RNP 0.30 DA		1196/45	403 (400-%)	

AUTHORIZATION REQUIRED

INDIANAPOLIS, INDIANA

Amdt 2 10NOV16

39°43'N-86°18'W

INDIANAPOLIS INTL (IND)

RNAV (RNP) Z RWY 32