

WAAS CH 50316 W16A	APP CRS 159°	Rwy Ldg TDZE 341 Apt Elev 341
--	------------------------	---

RNAV (GPS) RWY 16

HAWKINS FLD (HKS)

Baro-VNAV NA when using Jackson-Medgar Wiley Evers Intl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C (22°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Jackson-Medgar Wiley Evers Intl altimeter setting and increase all DA 19 feet and all MDA 20 feet. Increase LNAV/VNAV all Cats and LNAV Cats C/D visibilities ½ mile and Circling Cat C ¼ mile. For inop MALS when using Jackson-Medgar Wiley Evers Intl altimeter setting increase LNAV/VNAV all Cats to 1½.

MALS

MISSED APPROACH:
Climb to 2000 direct JILHO and hold.

ASOS 120.625	JACKSON APP CON ★ 123.9 319.2	HAWKINS TOWER ★ 119.65 (CTAF) 257.8	GND CON 121.9 239.0	CLNC DEL 121.9 (When twr closed)	UNICOM 122.95
------------------------	---	---	-------------------------------	---	-------------------------

4 NM Holding Pattern		OCARO		2000		JILHO			
2000		← 339°		→ 159°		*LNAV only.			
GP 3.00°		TCH 56		1900		*860			
6.9 NM		3.2 NM		1.5 NM					
CATEGORY	A	B	C	D					
LPV DA	542-½		201 (300-½)						
LNAV/VNAV DA	677-⅝		336 (400-⅝)						
LNAV MDA	780-½ 439 (500-½)		780-¾ 439 (500-¾)						
CIRCLING	860-1 519 (600-1)		880-1 539 (600-1)		1140-2¼ 799 (800-2¼)		1320-3 979 (1000-3)		

ELEV 341

TDZE 341

159°

9L

5387 X 150

0.3% UP

0.7% UP

3431 X 150

27

34

TWR

REIL Rwy 34

HIRL Rwy 16-34

MIRL Rwy 11-29

JACKSON, MISSISSIPPI
Amdt 2A 11DEC14

32°20'N-90°13'W

HAWKINS FLD (HKS)

RNAV (GPS) RWY 16