


SW-3, 06 AUG 2026 to 03 SEP 2026

TOP ALTITUDE:
9000

SOCAL DEP CON
125.2 323.275
D-ATIS DEP
135.65
CLNC DEL
120.35 327.0
CPDLC
GND CON
(N) 121.65 327.0
(S) 121.75 327.0
(W) 121.4 327.0
LOS ANGELES TOWER
(N) 133.9 239.3
(S) 120.95 379.1



IKAYE △

5400
282°
(14)

IKAYE TRANSITION (MOOOS2.IKAYE)

MOOOS
8000
4900

TAKEOFF MINIMUMS

Rwys 6L/R, 7L/R: NA-ATC.

Rwys 24L/R, 25L/R: Standard with minimum climb
of 500' per NM to 640.

NOTE: RADAR required.

NOTE: RNAV 1.

NOTE: Turboprop aircraft only.


NOTE: DME/DME/IRU or GPS required.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAYS 24L/R, 25L/R: Climb heading 251° to 640, then on heading 251° or as assigned by ATC, expect vectors to cross DTAIL at or above 3100, then on track 282° to cross MOOOS at or above 4900 and at or below 8000, thence. . .

. . . on (transition). Maintain 9000. Expect filed altitude five minutes after departure.

LOST COMMUNICATIONS: If not in contact with Departure Control within five minutes after departure, turn right and proceed direct MOOOS WP, climb to 9000' or filed altitude whichever is lower, and when able proceed direct filed or assigned route/fix/transition. Aircraft filing 10000 or above, climb to filed altitude ten minutes after departure.



NOTE: Chart not to scale.

SW-3, 06 AUG 2026 to 03 SEP 2026