

APP CRS
251°

Rwy Ldg
TDZE
122

Apt Elev
128

RNAV (RNP) Z RWY 24R

LOS ANGELES INTL (LAX)

▼

Simultaneous approach authorized with HHR. For uncompensated Baro-VNAV systems, procedure NA below 5°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 6000 and RNP 0.30 all Cats visibility to 1½ SM. Simultaneous approach authorized.

ALSF-2

Ⓐ

MISSED APPROACH: Climb to 2000 on track 251° to IGUPE and track 263° to RAFFS and hold.

D-ATIS	SOCAL APP CON	LOS ANGELES TOWER	GND CON
133.8	124.3 363.2 (APCH from W) 124.9 269.0 (090°-224°) 124.5 235.975 (225°-044°) 128.5 360.7 (045°-089°)	133.9 239.3 (N) 120.95 379.1 (S)	121.65 327.0 (N) 121.75 327.0 (S) 121.4 327.0 (W)

ELEV 128

D

TDZE 122

ROUTING TO BREEA
(not to scale)

BREEA

8000

251°

(3.6)

DECOR

9000

251°

(3.6)

SKOLL

10000

241°

(10.4)

CRUCS

14000

270K

12000

10000

274°

(10.9)

SEAVU

14000

270K

12000

2000

IGUPE

tr 251°

tr 263°

RAFFS

See planview for multiple IF locations.

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 73).

2000

IGUPE

tr 251°

2200

KOBEE

251°

2500

MUBME

251°

GP 3.00°

TCH 55

CATEGORY	A	B	C	D
RNP 0.15 DA	484/40	362 (400-¾)		
RNP 0.30 DA	586/60	464 (500-1½)		

TDZ/CL Rwy 6L, 7L, 24R, and 25L

HIRL all Rwy 5

AUTHORIZATION REQUIRED

LOS ANGELES, CALIFORNIA

Amtd 1D 07OCT21

33°57'N-118°24'W

LOS ANGELES INTL (LAX)

RNAV (RNP) Z RWY 24R