

LOC I-MCN

109.5

APP CRS

054°

Rwy Ldg

6221

TDZE

344

Apt Elev

354

ILS or LOC RWY 5

MIDDLE GEORGIA RGNL (MCN)

DME and RADAR required.

⚠

DME from MCN VORTAC. Simultaneous reception of I-MCN and MCN DME required. For inop ALS, increase S-ILS 5 Cat E visibility to RVR 4000 and S-LOC 5 Cats C, D, and E visibilities to 1 3⁄8 SM. * RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

AS

MISSED APPROACH: Climb to 800 then climbing right turn to 3000 on heading 090° and DBN VORTAC R-314 to TRUKR/DBN VORTAC 15 DME/RADAR and hold.

ATIS	ATLANTA APP CON ★	MACON TOWER ★	GND CON	UNICOM
120.775	124.2 279.6	128.2 (CTAF) 0 257.8	121.65	122.95

ELEV 354

TDZE 344

One Minute Holding Pattern

4800

2100

← 234°

→ 054°

GS 3.00°

TCH 56

800

3000

hdg 090°

DBN R-314

TRUKR DBN 15

ALLMN MCN 5.8

BRROS MCN 2.9

MCN 2.1

MCN 0.8

2000

1080

5.9 NM

2.9 NM

0.8 NM

1.4 NM

CATEGORY	A	B	C	D	E
S-ILS 5*	544/24 200 (200-½)				
S-LOC 5	840/24	496 (500-½)	840/50 496 (500-1)		
CIRCLING	900-1	546 (600-1)	920-1½ 566 (600-1½)	1120-2½ 766 (800-2½)	1180-3 826 (900-3)

STAR

14

23

32

054°

0.4% UP

6500 X 150

5000 X 150

HIRL Rwy 5-23

MIRL Rwy 14-32

REIL Rwy 23 and 32

MACON, GEORGIA

Amtd 4 08SEP22

32°42'N-83°39'W

MIDDLE GEORGIA RGNL (MCN)

ILS or LOC RWY 5