

LOC I-MSL 109.7	APP CRS 297°	Rwy Ldg TDZE 551 Apt Elev 551	ILS Z or LOC Z RWY 30 NORTHWEST ALABAMA RGNL (MSL)
---------------------------	------------------------	---	---

DME required. RADAR required.

▼



▲

DME from MSL DME.
Simultaneous reception of I-MSL and MSL DME required.
For inop ALS increase S-LOC 30 Cats C/D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 1200 then climbing right turn to 3000 on heading 020° to intercept RQZ VORTAC R-268 to JOBUM/RQZ VORTAC 42.5 DME/RADAR and hold, continue climb-in-hold to 3000.

ASOS 119.425	MEMPHIS CENTER 120.8 307.0	GCO 121.725	UNICOM 123.05 (CTAF) 0
------------------------	--------------------------------------	-----------------------	----------------------------------



	1200	3000	RQZ R-268	JOBUM RQZ 42.5 RADAR	MSL DME	HUPOK MSL 7 RADAR	One Minute Holding Pattern
		hdg 020°		DIXLI MSL 3.1	TICVU MSL 0.4 RADAR		
				MSL 4.6	MSL 5.6		
				1400	2300		
				1 NM	1.5 NM	2.8 NM	7.3 NM
CATEGORY	A		B		C		D
S-ILS 30	751-1/2		200 (200-1/2)				
S-LOC 30	920-1/2 369 (400-1/2)		920-5/8 369 (400-5/8)				
CIRCLING	1040-1 489 (500-1)		1280-2 729 (800-2)		1280-2 1/4 729 (800-2 1/4)		