

APP CRS	Rwy Ldg	8995
227°	TDZE	26
	Apt Elev	27

RNAV (RNP) Y RWY 23

NORFOLK INTL (ORF)

For uncompensated Baro-VNAV systems, procedure NA below -9°C (16°F) or above 54°C (130°F). GPS required. For inop ALS, increase RNP 0.10 DA visibility all Cats to 1½ SM, increase RNP 0.30 DA visibility all Cats to 1¾ SM.

MALSR

MISSED APPROACH: Climb to 2000 on track 227° to CALEY and hold.

ATIS 127.15	NORFOLK APP CON 118.9 353.7	NORFOLK TOWER 120.8 257.8	GND CON 121.9
----------------	--------------------------------	------------------------------	------------------

RADAR REQUIRED

MISSED APCH FIX

CALEY

045°

225°

4 NM

ELEV 27

TDZE 26

227°

9000 X 150

TWR

HIRL Rwy 5-23

(IAF) OMRI

(IF) JHALL

(FAF) BAAGN

HUXOL

GUTLE 190K

(IF) DULTS

5000 210K

5000 05° (7.5)

3200 05° (5.7)

1200 227° (7.3)

3000 197° (8.4)

227° (3.6)

1200 227° (2.2)

227° (12.5)

227° (7.5)

2300

MSA RW23 25 NM

2000	tr 227°	CALEY	See planview for multiple IF locations.	BAAGN
		△		1200
				1200
				GP 3.00°
				TCH 55
			3.6 NM	
CATEGORY	A	B	C	D
RNP 0.10 DA		432-¾	406 (500-¾)	
RNP 0.30 DA		491-1	465 (500-1)	
AUTHORIZATION REQUIRED				