

WAAS CH 50222 W05A	APP CRS 047°	Rwy Ldg 7809 TDZE 26 Apt Elev 26
--	------------------------	---

RNAV (GPS) Z RWY 5

NORFOLK INTL (ORF)

RNP APCH - GPS.

▼

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -4°C or above 54°C.

▲


For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500 and LNAV Cats C and D visibility to RVR 6000. *RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH:

Climb to 2000 direct
TECHI then on track 023°
to OUTLA and hold.

ATIS 127.15	NORFOLK APP CON 118.9 353.7	NORFOLK TOWER 120.8 257.8	GND CON 121.9
-----------------------	---------------------------------------	-------------------------------------	-------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).		2000	TECHI	tr 023°	OUTLA
2100		PEAAAY	1600	1.1 NM to RW05	
GP 3.00° TCH 56		6.4 NM	3.7 NM	1.1 NM	
CATEGORY	A	B	C	D	
LPV DA*	226/24		200 (200-½)		
LNAV/VNAV DA	306/24		280 (300-½)		
LNAV MDA	440/24 414 (500-½)		440/40 414 (500-¾)		
CIRCLING	480-1 454 (500-1)	540-1 514 (600-1)	540-1½ 514 (600-½)	900-2¾ 874 (900-2¾)	