



APP CRS	Rwy Ldg	11000
103°	TDZE	24
	Apt Elev	31

RNAV (RNP) Z RWY 10R

PORTLAND INTL (PDX)

RNP AR APCH - GPS. Authorization required. From DAYSS, CATUL, or TOWNN: RF.	ALSF-2 	MISSED APPROACH: Climb to 440 then climbing right turn to 5000 direct MULES and hold, continue climb-in-hold to 5000.
▼ For uncompensated Baro-VNAV systems, procedure NA below -5°C or above 54°C. Simultaneous approach authorized. For inop ALS, increase RNP 0.18 all Cats visibility to RVR 4500, increase RNP 0.30 all Cats visibility to RVR 5500.		

D-ATIS 128.35 269.9	PORTLAND APP CON 124.35 299.2	PORTLAND TOWER 118.7 257.8 (10L-28R) 123.775 251.125 (3-21, 10R-28L)	GND CON 121.9 348.6
------------------------	----------------------------------	--	------------------------



POWLZ	2000	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).	440	5000	MULES
2000	103°	See planview for multiple IF locations.			
GP 3.00°	TCH 53	6 NM			
CATEGORY	A	B	C	D	
RNP 0.18 DA		324/24	300 (300-½)		
RNP 0.30 DA		397/35	373 (400-¾)		
AUTHORIZATION REQUIRED					

NW-1, 06 AUG 2026 to 03 SEP 2026

NW-1, 06 AUG 2026 to 03 SEP 2026