



WAAS CH 40135 W33A	APP CRS 330°	Rwy Ldg TDZE 1424 Apt Elev 1430
--	------------------------	---

RNAV (GPS) RWY 33

JOE FOSS FLD (F'SD)

RNP APCH-GPS.		MISSED APPROACH: Climb to 3800 direct CEPOL and hold.		
⚠ ASR -30°C	Rwy 33 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, procedure NA below -22°C or above 54°C.			
ATIS 126.6	SIoux FALLS APP CON★ 125.8 284.725	SIoux FALLS TOWER★ 118.3(CTAF) 0 257.8	GND CON 121.9 348.6	UNICOM 122.95



3800	CEPOL	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 45).		FEZNT	4 NM Holding Pattern
		ZOTSU 2.6 NM to RW33	YUCNU 3100	330°	150° 6000 3800
		1.4 NM to RW33	2280	3100	GP 3.00° TCH 45
		1.4 NM	1.2	2.5 NM	6 NM
CATEGORY	A	B	C	D	
LPV DA	1729-7⁄8		305 (300-7⁄8)		
LNAV/VNAV DA	1974-1⁄8		550 (600-1⁄8)		
LNAV MDA	1920-1	496 (500-1)	1920-1³⁄8	496 (500-1³⁄8)	
CIRCLING	1960-1 530 (600-1)	1980-1 550 (600-1)	2060-1¾ 630 (700-1¾)	2200-2½ 770 (800-2½)	