

TAMPA, FLORIDA

ILS or LOC RWY 5

LOC I-MCF
109.5

APCH CRS
044°

Rwy Idg **11,421**
TDZE **10**
Arpt Elev **14**

AL-418 [USAF]

MACDILL AFB (KMCF)

RADAR or DME required.

*When ALS inop, increase RVR to 40, vis to ¾ mile.

**When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE RVR to 60, vis to 1½ miles.

ALSF-1

MISSED APPROACH: Climb to 2700 via MCF TACAN R-075 to MCF 22 DME and hold. Cross 8 DME at 1700. RNAV or ATC RADAR required for missed approach.

ATIS
133.825 270.1

TAMPA APP CON
124.95 354.0

TOWER
120.175 294.7

GND CON
118.575 275.8

***Circling not authorized NW of Rwy 5-23.

CAUTION:
LOC course offset 2.86° from the extended rwy centerline and intersects the rwy centerline 1834' after the DA.

WARNING: Use extreme caution PETER O. KNIGHT airport 4 NM Northeast of MACDILL AFB.

MACDILL
Chan 47 MCF

LOCALIZER 109.5
I-MCF
LOC offset 2.86°

EMASE
MCF 6.6
RADAR

(IF/IAF)
MILNE
MCF 15

Expect RADAR vectors around St. Petersburg
landmass for noise abatement, unless
otherwise requested by pilot.

EMERG SAFE ALT 100 NM 3000

ELEV 14

TDZE 10

offset
LOC

HIRL Rwy 5-23

CATEGORY	A	B	C	D	E
S-ILS 5 *	260/24 250 (300-½)				
S-LOC 5 **	420/24 410 (500-½)	420/40 410 (500-¾)			
*** CIRCLING	500-1 486 (500-1)	540-1 526 (600-1)	540-1½ 526 (600-1½)	580-2 566 (600-2)	1020-3 1006 (1100-3)

TAMPA, FLORIDA

27°51'N-82°31'W

MACDILL AFB (KMCF)

Amtd 1 18MAY23

ILS or LOC RWY 5

SE-3, 06 AUG 2026 to 03 SEP 2026

SE-3, 06 AUG 2026 to 03 SEP 2026