

LOC I-ALW <u>111.7</u>	APP CRS 202°	Rwy Ldg 6527 TDZE 1194 Apt Elev 1194
----------------------------------	------------------------	---

ILS or LOC RWY 20

DME required.

T DME from ALW VOR/DME. Simultaneous reception of I-ALW
A and ALW VOR/DME required. For inop ALS, increase S-LOC
20 Cat C/D visibility to 2½ SM.

#RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using Pendleton altimeter setting).

MALSR



MISSED APPROACH: Climb to 1800 then climbing right turn to 4000 on heading 346° and ALW VOR/DME R-314 to BACUN INT/ALW 15.4 DME and hold.

ASOS 135.875	SPOKANE APP CON ★ 133.15 379.15	WALLA WALLA TOWER ★ 118.5 (CTAF) 0 289.4	GND CON 121.6 289.4	UNICOM 122.95
-----------------	------------------------------------	---	------------------------	------------------

ALTERNATE MISSED
APCH FIX

113.75 PSC
R-070
Chan 84(Y)

PSC 40

(IAF)
HOLLOW INT

PSC 40

4600 to RIRRO
117° hdg (3.9)
and 202° (2)

4'

3200 ALW 12.3

ALW 8.7

ALW 7.2

21/19±

WALLA WALLA

Chan 111

RIRRO
AIW 123

8.7	1/00
-----	------

202		
3600		

	<u>GS 3.00°</u>
--	-----------------

← 3.6 NM →	
C	D

0-1/2)

80-13 786 (800-13)	REF
--------------------	-----

1000-2 ^{3/4})	1106 (1200-3)	HIR
-------------------------	---------------	-----

IL

WALLA WALLA, WASHINGTON
Amdt 1A 08SEP22

46°06'N-118°17'W

WALLA WALLA RGNL (ALW)
S or LOC RWY 20

REIL Rwy 2 **L**
HIRL Rwy 2-20 **L**

WALLA WA

US or IC

TEST OF ES

NW-1, 06 AUG 2026 to 03 SEP 2026

NW-1, 06 AUG 2026 to 03 SEP 2026