

LOC/DME I-JAC

109.1

Chan 28

APP CRS

187°

Rwy Ldg

6300

TDZE

6451

Apt Elev

6451

ILS Z or LOC Z RWY 19

JACKSON HOLE (JAC)

DME required for LOC only. RNAV 1-GPS required. RADAR required for procedure entry at MOSSS.

▼

▲

❄

Circling NA for Cats A, B, and C east of Rwy 1-19. Inop table does not apply to S-ILS 19*. Circling NA for Cat D. For inop ALS increase S-LOC 19# Cats C and D visibility to RVR 4500.

MALS

⏏

A4

MISSED APPROACH: Climb to 6900 then climbing right turn to 14000 on JAC VOR/DME R-192 to KICNE INT/JAC 26.6 DME and hold, continue climb-in-hold to 14000.

*Missed approach requires minimum climb of 225 feet per NM to 9400; if unable to meet climb gradient, see ILS Y or LOC Y RWY 19.

#Missed approach requires minimum climb of 234 feet per NM to 9600; if unable to meet climb gradient, see ILS Y or LOC Y RWY 19.

D-ATIS	SALT LAKE CENTER	JACKSON TOWER*	GND CON	UNICOM
120.625	133.25 285.6	118.075 (CTAF) 0	124.55	122.95

6900	14000	KICNE	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 53).				ZOSUV	ZIBIV
JAC R-192			YUSGU	WOMRU				
I-JAC 1.2		I-JAC 1.9	SOSUE I-JAC 4.5	I-JAC 5.9	8000	205°	232°	11000
0.7		2.6 NM	1.4 NM	2.7 NM	4 NM	4.3 NM		
CATEGORY	A	B	C	D				
S-ILS 19*		6651/40	200 (200-¾)					
S-LOC 19#		6720/40	269 (300-¾)					
CIRCLING	6840-1 389 (400-1)	6960-1 509 (600-1)	7440-3 989 (1000-3)	NA				

TWR

4300 X 150

0.6% UP

CL Rwy 1-19

HIRL Rwy 1-19

JACKSON, WYOMING

Amtd 2 20APR23

43°36'N-110°44'W

JACKSON HOLE (JAC)

ILS Z or LOC Z RWY 19