



ILS or LOC RWY 13

LOC I-OVI 110.35	APCH CRS 128°	Rwy Idg TDZE Arpt Elev 8194 4294 4295	[USAF]	CANNON AFB (KCVS)
RADAR or DME required. Missed approach requires use of RNAV or RADAR monitoring.			MALSR (A5)	MISSED APPROACH: Climb to 6000 out CVS TACAN R-1305.6 DME (HOMEP) then climbing right turn to 7000 intercept CVS R-193 to 12 DME (CLINK) and hold.
* When ALS inop, increase vis to ¾ mile. ** When ALS inop, increase CAT AB vis to 1 mile; CAT CDE vis to 1¾ miles.				


ATIS 119.1 269.9	APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8
----------------------------	---------------------------------	------------------------------	-------------------------------



EMERG SAFE ALT 100 NM 8000



CATEGORY	A	B	C	D	E
S-ILS 13 *	4544-½		250	(300-½)	
S-LOC 13**	4760-½ 466 (500-½)		4760-1 466 (500-1)		
CIRCLING	4840-1 545 (600-1)		4860-1½ 565(600-1½)	5000-2¼ 705(800-2¼)	5020-2½ 725(800-2½)



ILS or LOC RWY 13

SW-1, 06 AUG 2026 to 03 SEP 2026

SW-1, 06 AUG 2026 to 03 SEP 2026