

ILS or LOC RWY 31

LOC I-BNN 108.3	APCH CRS 308°	Rwy Idg TDZE 4270 Arprt Elev 4295	[USAF]	CANNON AFB (KCVS)
---------------------------	-------------------------	---	--------	-------------------

RADAR or DME required. Missed approach requires use of RNAV or RADAR monitoring.

▲ * When ALS inop, increase vis to ¾ mile.

ATIS 119.1 269.9	APP CON 118.425 352.1	TOWER 120.4 270.25	GND CON 121.9 275.8
----------------------------	---------------------------------	------------------------------	-------------------------------

****** When ALS inop, increase CAT AB vis to 1 mile, CAT CDE vis to 1 ½ miles.

EMERG SAFE ALT 100 NM 9000

6000 ↑	LERAY CVS 5.5	7000 ↶	CLUNK CVS 12	VGS1 TCH (41') and the procedure TCH (51') is greater than 3'.
-----------	---------------	-----------	--------------	--

CATEGORY	A	B	C	D	E
S-ILS 31*	4470-½ 200 (200-½)				
S-LOC 31**	4660-½ 390 (400-½) 4660-⅝ 390 (400-⅝)				
CIRCLING	4840-1				
	545 (600-1)	4860-1½ 565 (600-1½)	5000-2¼ 705 (800-2¼)	5020-2½ 725 (800-2½)	

ELEV 4295	TDZE 4270
-----------	-----------

HIRL all rwys

FAF to MAP 4.9 NM				
Knots	60	90	120	150
Min:Sec	4:54	3:16	2:27	1:58