

WAAS CH 65713 W23B	APP CRS 234°	Rwy Ldg 7500 TDZE 435 Apt Elev 435
--	------------------------	---

RNAV (GPS) Y RWY 23L

RALEIGH-DURHAM INTL (RDU)

RNP APCH-GPS.

T Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C or above 54°C.


A Use of FD or AP required during simultaneous operations. For inop ALS, increase LNAV Cat C/D visibility to 1 3/8 SM.

MALSR



MISSED APPROACH:
Climb to 1100 then
climbing left turn to
2600 direct ZEBUL
and hold.

D-ATIS 123.8	RALEIGH APP CON 127.675 307.9	RALEIGH TOWER 127.45 257.8	GND CON 121.9 348.6	CLNC DEL 120.1	CPDLC
-----------------	----------------------------------	-------------------------------	------------------------	-------------------	-------



CATEGORY	A	B	C	D
LPV DA	635/18		200 (200-½)	
LNAV/VNAV DA	820/35		385 (400-¾)	
LNAV MDA	920/24	485 (500-½)	920/50	485 (500-1)
CIRCILING	960-1	525 (600-1)	1020-1½ 585 (600-1½)	1180-2½ 745 (800-2½)

REIL Rwy 32
MIRL Rwy 14-32
HIRM Wrys 5R-23L and 5L-23R
TDZ/CL Wrys 5L, 23R, and 23L