

WAAS CH 62829 W18A	APP CRS 175°	Rwy Ldg TDZE 492 Apt Elev 542
--	------------------------	---

RNAV (GPS) Y RWY 18L

AUSTIN-BERGSTROM INTL (AUS)


RNP APCH-GPS.

Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -5°C or above 54°C. Use of FD or AP required during simultaneous operations. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV visibility all Cats to RVR 6000, and LNAV visibility Cats C, D, and E to RVR 6000.

ALSF-2

MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct HOOKK and hold.

D-ATIS 124.4	AUSTIN APP CON 127.225 317.65 (E) 120.875 270.25 (S) 119.0 370.85 (W)	AUSTIN TOWER 121.0 281.5	GND CON 121.9 348.6
------------------------	---	------------------------------------	-------------------------------



RRTOO

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 74).

DDTOO

1000

3000

HOOKK

2500

175°

1600

1.1 NM to RW18L

RW18L

GP 3.00°

TCH 61

3 NM

2.2 NM

1.1 NM

CATEGORY	A	B	C	D	E
LPV DA	692/18 200 (200-½)				
LNAV/VNAV DA	906/40 414 (400-¾)				
LNAV MDA	900/24 408 (400-½)	900/40 408 (400-¾)			
CIRCLING	1040-1 498 (500-1)	1120-1 578 (600-1)	1200-1¾ 658 (700-1¾)	1200-2 658 (700-2)	NA

ELEV 542

TDZE 492

18R

0.6% DOWN

12250 X 150

0.3% UP

36L

175°

18L

TWR

9000 X 150

36R

HIRL Rwy 18L-36R and 18R-36L

TDZL/RCLS Rwy 18L and 36R