

WAAS CH 72625 W23A	APP CRS 229°	Rwy Ldg 9020 TDZE 582 Apt Elev 589
--	------------------------	---


RNAV (GPS) RWY 23
TERRE HAUTE RGNL (HUF)

RNP APCH.


T Baro-VNAV and VDP NA when using Paris allimeter setting. Rwy 23 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local allimeter setting not received, use Paris allimeter setting and increase all DA 61 feet and all MDA 80 feet, increase LPV and LNAV/VNAV visibility all Cats $\frac{1}{8}$ SM, increase LNAV and Circling Cats C/D visibilities $\frac{1}{8}$ SM.

MISSED APPROACH:
Climb to 2600 direct
POKHY and hold.

ATIS 127.5 269.375	HULMAN APP CON 125.45 339.8	HULMAN TOWER 134.725 322.475	GND CON 121.6 348.6
-----------------------	--------------------------------	---------------------------------	------------------------



ELEV 589	D	TDZE 582
----------	----------	----------



TERRE HAUTE, INDIANA
Amdt 1E 25FEB21

39°27'N-87°18'W

TERRE HAUTE RGNL (HUF)
RNAV (GPS) RWY 23