

WAAS CH 63147 W28A	APP CRS 280°	Rwy Ldg TDZE 588 Apt Elev 592
--	------------------------	---

RNAV (GPS) RWY 28

NIAGARA FALLS INTL (IAG)

RNP APCH - GPS.

▼

▲


For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.
Rwy 28 helicopter visibility reduction below RVR 4000 not authorized.
Circling Rwy 6 NA at night.
Circling NA for Cat E southeast of Rwy 6-24.
Inop table does not apply to LPV all Cats.
For inop ALS, increase LNAV/VNAV visibility all Cats to RVR 4500, LNAV visibility all Cats to RVR 5500.

MALSRL

MISSED APPROACH:

Climb to 1040 then climbing right turn to 3600 direct ZUPUV and hold, continue climb-in-hold to 3600.

ATIS 120.8 269.4	BUFFALO APP CON 126.5 317.6	NIAGARA TOWER ★ 118.5 (CTAF) 0 349.0	GND CON 125.3 275.8	UNICOM 122.95
----------------------------	---------------------------------------	--	-------------------------------	-------------------------



ELEV **592** **D** TDZE **588**

280°

1040 3600 ZUPUV

VGSI and RNAV glidepath not coincident (VGSI Angle 2.50/TCH 67).

APIWO KIGUW CUVTU

1.2 NM to RW28 2.9 NM to RW28 2300 280° 100° 6000 3100

GP 3.00° TCH 55

CATEGORY	A	B	C	D	E
LPV DA	838/40 250 (300-¾)				
LNAV/VNAV DA	957/40 369 (400-¾)				
LNAV MDA	960/40 372 (400-¾)				
CIRCLING	1100-1	508 (600-1)	1280-2 688 (700-2)	1280-2¼ 688 (700-2¼)	1280-2½ 688 (700-2½)

REIL Rwy 6 and 24 **Ⓛ**

TDZL/RCLS Rwy 28 **Ⓛ**

RCLS Rwy 10 **Ⓛ**

HIRL Rwy 10-28 **Ⓛ**

MIRL Rwy 6-24 **Ⓛ**

NIAGARA FALLS, NEW YORK

43°07'N-78°57'W

NIAGARA FALLS INTL (IAG)

Orig 27NOV25

RNAV (GPS) RWY 28