



APP CRS	Rwy Ldg	8587
126°	TDZE	46
	Apt Elev	62

RNAV (RNP) Z RWY 12R
NORMAN Y MINETA SAN JOSE INTL (SJC)

RNP AR APCH-GPS. ▼ For uncompensated Baro-VNAV systems, procedure NA below 0°C or above 54°C. For inop ALS, increase RNP 0.15 all Cats visibility to RVR 5500.			MALSR MISSED APPROACH: Climb to 4600 on track 126° to HOSBO and track 124° to GILRO and hold.
D-ATIS 126.95	NORCAL APP CON 120.1 290.25	SAN JOSE TOWER ★ 124.0 (CTAF) 0 257.6	GND CON 121.7
			UNICOM 122.95



MISSD APCH FIX 5 NM GILRO		HOSBO 124° (17.2)				
FOXAG 1100 GP 3.00° TCH 58		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 75).		4600 ↑ tr 126°	HOSBO ★ tr 124°	GILRO △
See planview for multiple IF locations.						
3.2 NM						
CATEGORY	A	B	C	D		
RNP 0.15 DA	394/30 348 (400-¾)					
RNP 0.30 DA	486/40 440 (500-¾)					
AUTHORIZATION REQUIRED						

SW-2, 06 AUG 2026 to 03 SEP 2026

SW-2, 06 AUG 2026 to 03 SEP 2026