




WAAS CH 90201 W22A	APP CRS 226°	Rwy Ldg TDZE 980 Apt Elev 980	7004
--	------------------------	---	-------------

RNAV (GPS) RWY 22
BLUE GRASS (LEX)

RNP APCH - GPS.			MISSED APPROACH: Climb to 3000 direct RYYYE and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Baro-VNAV and VDP NA when using FFT altimeter setting. When local altimeter setting not received, use FFT altimeter setting and increase LPV DA to 1242 feet and all visibilities 1/8 SM. Increase LNAV/VNAV DA to 1333 feet and all visibilities 1/8 SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D 1/4 SM, and Circling visibility Cat C/D 1/4 SM.			
ATIS 126.3	LEXINGTON APP CON 120.15 259.3 (040°-220°) 120.75 298.9 (221°-039°)	LEXINGTON TOWER 119.1 257.8	GND CON 121.9



CATEGORY	A	B	C	D
LPV DA		1180-3/4	200 (200-3/4)	
LNAV/VNAV DA		1271-7/8	291 (300-7/8)	
LNAV MDA		1360-1	380 (400-1)	
CIRCLING	1440-1	460 (500-1)	1520-1 1/2 540 (600-1 1/2)	1600-2 620 (700-2)



SE-1, 06 AUG 2026 to 03 SEP 2026

SE-1, 06 AUG 2026 to 03 SEP 2026