

RNAV (GPS) RWY 24
DECATUR (DEC)

DECLARATION (DEC)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C.
 ▲ Baro-VNAV and VDP NA when using Logan County altimeter setting.
 When local altimeter setting not received, use Logan County altimeter setting; increase LPV DA to 1012 feet and visibility all Cats $\frac{1}{4}$ mile, LNAV/VNAV DA to 1168 feet and visibility all Cats $\frac{1}{4}$ mile; increase all MDA 80 feet and LNAV visibility Cats C/D $\frac{3}{8}$ mile, Circling visibility Cats C/D $\frac{1}{4}$ mile.

MISSED APPROACH:
Climb to 2300 direct
FIKDO and hold.

Procedure NA for arrivals at EWITT on V313 northbound, V233 northeast bound.

(IAF) EWITT

2800 NoPT
157°
(17.9)

(IAF) LODGE

2800 NoPT
204°
(13.7)

4 NM

Procedure NA for arrivals at REGOY on V251 northeast bound.

(FAF) PEDIC

2300
240°
(6.1)

(IF/IAF) ZOLIP

2800 NoPT
300°
(4.9)

(IAF) REGOY

796±

RW24

ZINOB
2.4 NM to RW24

MSA RW24 25 NM

3100

FIKDO

FIKDO



060° 240° 4 NM