

APP CRS
085°

Rwy Ldg
TDZE
Apt Elev
5797
808
841

RNAV (RNP) Z RWY 8
FULTON COUNTY EXEC/CHARLIE BROWN FLD (F'TY)

▼

For uncompensated Baro-VNAV systems, procedure NA below -11°C or above 54°C. Ridge with trees to 1299' MSL between FAF and runway threshold may be obscured by clouds even with airfield ceiling at or above procedure minimums.

MALSR

MISSED APPROACH: Climb to 1600 then climbing left turn to 3000 direct MIKEE and hold.

ATIS 120.175	ATLANTA APP CON 121.0 268.7	FULTON COUNTY TOWER 118.45 257.8	GND CON 121.7 348.6
------------------------	---------------------------------------	--	-------------------------------

Diagram illustrating the RNP (RNP) Z RWY 8 approach. The path starts at (IAF) TIINI, proceeds to (IF) CAVEB, then to (FAF) FABMA, and finally to RW08. Key altitudes and distances are marked: 3000 ft at TIINI, 3000 ft at CAVEB, 3000 ft at FABMA, and 1004 ft at RW08. Distances are 4 NM from TIINI to CAVEB, 5.9 NM from CAVEB to FABMA, and 6.7 NM from FABMA to RW08. A missed approach procedure is shown: Climb to 1600 then climbing left turn to 3000 direct MIKEE and hold. A circular inset shows the MSA RW08 2.5 NM with a 3100 ft MSL.

CAVEB

FABMA

RW08

3000

3000

3000

GP 3.00°

TCH 60

8.8 NM

6.7 NM

1600

3000

MIKEE

085°

5797 X 100

26

TWR

☆

CATEGORY	A	B	C	D
RNP 0.30 DA	1401-1¼ 593 (600-1¼)			

AUTHORIZATION REQUIRED

HIRL Rwy 8-26

REIL Rwy 26

ATLANTA, GEORGIA
Amdt 2 30JAN20

FULTON COUNTY EXEC/CHARLIE BROWN FLD (F'TY)
33°47'N-84°31'W

RNAV (RNP) Z RWY 8