

LOC I-GGG	APP CRS	Rwy Ldg	9200
109.5	131°	TDZE	358
		Apt Elev	366

ILS or LOC RWY 13
EAST TEXAS RGNL (GGG)



DME required.

▼ VDP NA when using JXI altimeter setting. For inop ALS, increase S-ILS 13 Cat E visibility to RVR 4000, S-LOC 13 Cat C/D/E visibility to 1 3/8 SM. When local altimeter setting not received, use JXI altimeter setting and increase S-ILS 13 DA to 617 feet; increase all MDAs 60 feet, and S-LOC 13 visibility Cat C/D to RVR 6000 and Circling visibility Cat C/D/E 1/4 SM. *RVR 1800 authorized with use of FD or AP or HUD to DA (NA when using JXI altimeter setting).

MALSR

MISSED APPROACH: Climb to 3000 on GGG VORTAC R-126 to ARGEN INT/GGG 1.4 DME and hold, continue climb-in-hold to 3000.

ATIS 119.65	LONGVIEW APP CON* 124.675 257.975	EASTEX TOWER* 119.2 (CTAF) 0377.05	GND CON 121.6	UNICOM 122.95
----------------	--------------------------------------	---------------------------------------	------------------	------------------



CATEGORY				
S-ILS 13*				
558/24 200 (200-1/2)				
S-LOC 13				
860/24 502 (500-1/2) 860/55 502 (500-1) 860/60 502 (500-1 1/4)				
CIRCLING				
860-1 494 (500-1) 980-1 3/4 614 (700-1 3/4) 1080-2 1/4 714 (800-2 1/4) 1080-2 1/2 714 (800-2 1/2)				

SC-2, 06 AUG 2026 to 03 SEP 2026

SC-2, 06 AUG 2026 to 03 SEP 2026