

WAAS CH 50131 W18A	APP CRS 178°	Rwy Ldg 9400 TDZE 35 Apt Elev 36
--	------------------------	---

RNAV (GPS) Y RWY 18R
VALLEY INTL (HRL)

RNP APCH - GPS.


V For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1°C or above 54°C.
A For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4000, LNAV Cats C and D visibility to RVR 5500. When local altimeter setting not received, use Port Isabel altimeter setting and increase LPV DA to 277 feet; increase LNAV/VNAV DA to 327 feet; increase all MDAs 60 feet and LNAV visibility Cat C/D to RVR 4000 and Circling visibility Cat C/D ¼ SM. For inop ALS when using Port Isabel altimeter setting, increase LNAV/VNAV all Cats visibility to RVR 4500. Baro-VNAV and VDP NA when using Port Isabel altimeter setting.
 * RVR 1800 authorized with use of FD or AP or HUD to DA, (NA when using Port Isabel altimeter setting).

MALSR




MISSED APPROACH:
Climb to 500 then
climbing left turn to
2000 direct RELAX
and hold

ATIS 124.85	VALLEY APP CON 120.7 279.5	HARLINGEN TOWER★ 119.3 (CTAF) 0 317.6	GND CON 121.7	UNICOM 122.95
----------------	-------------------------------	--	------------------	------------------



ELEV 36	D	TDZE 35
---------	----------	---------



HARLINGEN, TEXAS

Amdt 3 11JUL24

500 2000 RELAX △

See planview for multiple IF locations.

0.9 NM to RW18R

RW18R

WEVEN 1.5 NM to RW18R

CIXEN 1400

178°

1600

1400

GP 3.00° TCH 55

0.9 NM 0.6 NM 2.6 NM 1.3 NM

CATEGORY	A	B	C	D
LPV DA *	235/24	200 (200-½)		
LNAV/DA	285/24	250 (300-½)		
LNAV MDA	400/24	365 (400-½)	400/35	365 (400-⅔)
CIRCLING	460-1 424 (500-1)	560-1 524 (600-1)	600-1½ 564 (600-½)	680-2 644 (700-2)

VALLEY INTL (HRL)

26°14'N-97°39'W

RNAV (GPS) Y RWY 18R