

WAAS CH 62901 W05A	APP CRS 051°	Rwy Ldg TDZE 759 Apt Elev 782	6002
--	------------------------	---	-------------

RNAV (GPS) RWY 5

ANDERSON RGNL (AND)


RNP APCH - GPS.

VDP NA when using Clemson altimeter setting. When local altimeter setting not received, use Clemson altimeter setting and increase LPV DA to 1006 feet; increase all MDAs 60 feet and LNAV visibility Cats C/D ¼ SM. Circling visibility Cats C/D ¼ SM. Circling Rwy 17, 35 NA at night. For inop ALS when using Clemson altimeter setting, increase LNAV visibility Cats C/D to 1½ SM.

MALSR

MISSED APPROACH: Climb to 3000 direct OXTIC and hold.

ASOS 120.675	GREER APP CON★ 118.8 270.275	CTAF 123.60
------------------------	--	-----------------------



4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 49).		3000	OXTIC
OYUNA		OWUXO		RW05	
6000 2500		2500		1.3 NM to RW05	
GP 3.00° TCH 54		2500		RW05	
231°		051°		051°	
6 NM		4.1 NM		1.3 NM	
CATEGORY	A	B	C	D	
LPV DA	959-½		200 (200-½)		
LNAV MDA	1200-½	441 (500-½)	1200-7/8	441 (500-7/8)	
CIRCLING	1260-1 478 (500-1)	1320-1 538 (600-1)	1440-1¾ 658 (700-1¾)	1500-2¼ 718 (800-2¼)	

