

WAAS
CH **86519**
W05A

APP CRS
053°

Rwy Ldg
TDZE **1297**
Apt Elev **1297**

RNAV (GPS) RWY 5

MANSFIELD LAHM RGNL (MF'D)

RNP APCH

⚠

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F).

MISSED APPROACH: Climb to 3000 direct NANNI and hold.

ATIS
125.3

CLEVELAND APP CON ★
128.35 360.65

MANSFIELD TOWER ★
119.8 (CTAF) 291.775

GND CON
121.8 291.775

UNICOM
122.95

The main approach chart for RNAV (GPS) RWY 5 at Mansfield, Ohio. It shows the following features:

- DUSKY**: Initial approach fix, 3000 ft, 120° heading, 20.8 NM.
- HUDOR**: (IAF) Fix, 3000 ft, 14.3° heading, 6.3 NM.
- JOKAM**: (IF/IAF) Fix, 2700 ft, 053° heading, 4 NM.
- ZOLEL**: (FAF) Fix, 2700 ft, 053° heading, 1.6 NM.
- YOGUD**: (IAF) Fix, 2700 ft, 233° heading, 6.3 NM.
- WOVOM**: 2.3 NM to RW05, 1564 ft.
- NANNI**: Missed approach fix, 4 NM, 053° heading, 233° heading.
- MSA RW05 25 NM**: Minimum Safe Altitude for RW05, 3000 ft.

4 NM Holding Pattern JOKAM

3000

233°

053°

GP 3.00°

TCH 50

2700

053°

2060

6 NM

2 NM

0.8

1.5 NM

3000

NANNI

*LNAV only.

*1.5 NM to RW05

RW05

CATEGORY	A	B	C	D
LPV DA	1547-7/8		250 (300-7/8)	
LNAV/VNAV DA	1590-1		293 (300-1)	
LNAV MDA	1820-1 523 (600-1)		1820-1½ 523 (600-1½)	
CIRCLING	1820-1 523 (600-1)		2000-2 703 (800-2) 2000-2¼ 703 (800-2¼)	

HIRL Rwy 5-23 and 14-32

REIL Rwy 5 and 23

MANSFIELD, OHIO
Amdt 1A 13SEP18

40°49'N-82°31'W

MANSFIELD LAHM RGNL (MF'D)
RNAV (GPS) RWY 5

EC-2, 06 AUG 2026 to 03 SEP 2026

EC-2, 06 AUG 2026 to 03 SEP 2026