

WAAS CH 42700 W28A	APP CRS 281°	Rwy Idg TDZE Apt Elev	6003 85 85
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 28


MILLVILLE MUNI (MIV)

RNP APCH-GPS.

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Atlantic City altimeter setting and increase all DA/MDA 60 feet; increase LNAV/VNAV all Cats, LNAV Cats C/D and Circling Cat C visibility ¼ mile. VDP and Baro-VNAV NA when using Atlantic City altimeter setting.

MISSED APPROACH: Climb to 2000 direct TIYDU and right turn on track 030° to RUPDE and right turn 077° track to VCN VOR/DME and hold.

ASOS 119.6	ATLANTIC CITY APP CON 124.6 327.125	UNICOM 123.0 (CTAF) 0
----------------------	---	---------------------------------



	2000 ↑	TIYDU ✧	tr 030°	RUPDE ✧	tr 077°	VCN ◻	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/ TCH 29)
	CATEGORY						
	LPV DA						
	LNAV/ VNAV DA						
	LNAV MDA						
	CIRCLING						
	MIRL Rwys 10-28 and 14-32 0						