



WAAS CH 86212 W22A	APP CRS 219°	Rwy Ldg TDZE 322 Apt Elev 322
--	------------------------	---

RNAV (GPS) RWY 22
MILLINGTON/MEMPHIS (NQA)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 840 then climbing right turn to 2500 direct ZIVNY and hold.	
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. ▲ For inop ALS, increase LPV Cat E visibility to ¾ SM, LNAV/VNAV all Cats visibility to 1½ SM, and LNAV Cat E visibility to 1½ SM.				
AWOS-3 118.925	MEMPHIS APP CON 119.1 291.6 125.8 338.3 (176°-355°) (356°-175°)	MILLINGTON TOWER ★ 120.25 (CTAF) 0 340.2	GND CON 121.375	UNICOM 122.95



840		2500	ZIVNY	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 67).		7 NM Holding Pattern		
CATEGORY	A		B		C		D	E
LPV DA			522-½		200 (200-½)			
LNAV/VNAV DA			784-1		462 (500-1)			
LNAV MDA	780-½ 458 (500-½)				780-¾ 458 (500-¾)			
CIRCLING	800-1 478 (500-1)		820-1 498 (500-1)		920-1½ 598 (600-1½)		960-2 638 (700-2)	960-2¼ 638 (700-2¼)

SE-1, 06 AUG 2026 to 03 SEP 2026

SE-1, 06 AUG 2026 to 03 SEP 2026