

WAAS
CH **49147**
W23B

APP CRS
229°

Rwy Ldg
TDZE **184**
Apt Elev **187**

RNAV (GPS) X RWY 23
MORRISTOWN MUNI (MMU)

RNP APCH - GPS.
⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Circling to Rwy 13, 31 NA at night. For inop ALS, increase LPV all Cats visibility to 7% and LNAV Cats C/D visibility to 1¾ SM.

MALSR
⚠


MISSED APPROACH: (Do not exceed 185K until BSPUR) Climb to 700 then climbing right turn to 3000 direct BSPUR and track 012° to EMRSN and hold.
* Missed approach requires minimum climb of 201 feet per NM to 1900.

ATIS
124.25

NEWARK APP CON
127.6 379.9

MORRISTOWN TOWER ★
118.1 (CTAF) **353.9**

GND CON
134.2



ELEV 187	TDZE 184
----------	----------

CATEGORY	A	B	C	D
LPV DA *		384-1½	200 (200-½)	
LPV DA		436-1½	252 (300-½)	
LNAV/VNAV DA		774-1¼	590 (600-1¼)	
LNAV MDA	760-½	576 (600-½)	760-1¼	576 (600-1¼)
CIRCLING	860-1 673 (700-1)	900-1 713 (800-1)	1000-2½ 813 (900-2½)	1240-3 1053 (1100-3)