

WAAS CH 87006 W22A	APP CRS 224°	Rwy Ldg TDZE Apt Elev	7301 913 913
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 22

CHIPPEWA VALLEY RGNL (EAU)

RNP APCH.

Baro-VNAV and VDP NA when using Rice Lake altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. When local altimeter setting not received, use Rice Lake altimeter setting and increase LPV DA to 1223, LNAV/VNAV DA to 1285, and increase LNAV/VNAV visibility all Cats ¼ SM; increase all MDA 120 feet and LNAV Cats C/D visibility ¾ SM and Circling Cat C visibility ¼ SM. For inop ALS increase LNAV/VNAV visibility all Cats to ¾ SM and LNAV Cats C/D visibility to 1 SM. For inop ALS when using Rice Lake altimeter setting increase LPV visibility all Cats to 1 SM and LNAV Cats C/D visibility to 1 ¾ SM.

MALSRLAS

MISSED APPROACH:
Climb to 1320 then climbing right turn to 3500 direct IROKE and hold.

ATIS 126.025	MINNEAPOLIS CENTER 125.3 335.6	EAU CLAIRE TOWER ★ 118.575 (CTAF) 0	GND CON 120.925
------------------------	--	---	---------------------------

ELEV 913 D TDZE 913

1320 3500 IROKE

*LNAV only

CAVUX 1.9 NM to RW22

*0.9 NM to RW22

RW22

0.9 NM 1 NM 4.2 NM 6 NM

224°

8101 X 150 0.6% DOWN

TWR 32

HIRL Rwy 4-22

MIRL Rwy 14-32

REIL Rwy 4 and 14

IROKE 4 NM Holding Pattern				
044° → 6000 ← 224° 3500				
GP 3.00° TCH 50				
CATEGORY	A	B	C	D
LPV DA	1113-½		200 (200-½)	
LNAV/VNAV DA	1175-½		262 (300-½)	
LNAV MDA	1260-½	347 (400-½)	1260-⅝	347 (400-⅝)
CIRCLING	1480-1 567 (600-1)	1540-1 627 (700-1)	1660-2¼ 747 (800-2¼)	2200-3 1287 (1300-3)

EAU CLAIRE, WISCONSIN

Amdt 2 03JAN19

44°52'N-91°29'W

CHIPPEWA VALLEY RGNL (EAU)

RNAV (GPS) RWY 22