

APP CRS	Rwy Ldg	7302
316°	TDZE	806
	Apt Elev	808

RNAV (GPS) RWY 32
SOUTHERN WISCONSIN RGNL (JVL)

RNP APCH-GPS.	 Circling Rwy 18 NA at night. Baro-VNAV and VDP NA when using Rockford altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -16° C or above 54°C. When local altimeter setting not received, use Rockford altimeter setting and increase LNAV/VNAV DA to 1289 feet and all MDAs 80 feet; increase LNAV/VNAV all Cats visibility ¼ SM, LNAV Cat C/D visibility ½ SM, and Circling Cat C/D visibility ¼ SM. For inop ALS when using Rockford altimeter setting, increase LNAV/VNAV all Cats visibility and LNAV Cat C/D visibility to 1¾ SM.	MALSR	 MISSED APPROACH: Climb to 3100 direct TAYOR and hold.
---------------	--	-------	--

ATIS 128.25	ROCKFORD APP CON 121.0 327.0	JANESVILLE TOWER ★ 118.8 (CTAF) 225.4	GND CON 121.65	UNICOM 122.95
-----------------------	--	---	--------------------------	-------------------------

REIL Rwy 14 and 22 ①
MIRL Rwy 18-36 ①
HIRL Rwy 4-22 and 14-32 ①

3100 ↑ TAYOR

*LNAV only.

RW32

JODER 2600

TIRRO

4 NM Holding Pattern

136° → 6000
← 316° 3100

GP 3.00°
TCH 52

CATEGORY	A	B	C	D
LNAV/VNAV DA	1220-3/4 414 (500-3/4)			
LNAV MDA	1200-1/2 394 (400-1/2)		1200-5/8 394 (400-5/8)	
CIRCLING	1260-1 452 (500-1)	1320-1 512 (600-1)	1420-13/4 612 (700-13/4)	1460-2 652 (700-2)

JANESVILLE, WISCONSIN
Orig-D 16JUN22

SOUTHERN WISCONSIN RGNL (JVL)
RNAV (GPS) RWY 32

EC-3, 06 AUG 2026 to 03 SEP 2026

EC-3, 06 AUG 2026 to 03 SEP 2026

42°37'N-89°02'W