

WAAS CH 61015 W06A	APP CRS 063°	Rwy Ldg TDZE 1107 Apt Elev 1156
--	------------------------	---

RNAV (GPS) RWY 6

FORT DODGE RGNL (FOD)

RNP APCH.

▼


▲

Baro-VNAV NA when using Webster City altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. VDP NA when using Webster City altimeter setting. When local altimeter setting not received, use Webster City altimeter setting: increase LPV DA to 1349 feet; increase LNAV/VNAV DA to 1567 feet and all Cats visibility ¼ SM; increase all MDAs 60 feet and LNAV Cats C/D and Circling Cat C visibility ¼ SM. For inoperative MALSR when using Webster City altimeter setting, increase LPV all Cats visibility to 1 mile.

MALSR

MISSED APPROACH:
Climb to 3000 direct
OXDAH and hold.

AWOS-3PT 118.775	MINNEAPOLIS CENTER 134.0 288.3	UNICOM 123.0 (CTAF)
----------------------------	--	-------------------------------



ELEV 1156 TDZE 1107	
4 NM Holding Pattern 3000 ←243° 063°→ GP 3.00° TCH 54 GEGQI EYROV RW06 OXDAH *1.2 NM to RW06 *LNAV only.	
CATEGORY	A B C D
LPV DA	1307-½ 200 (200-½)
LNAV/VNAV DA	1525-1 418 (400-1)
LNAV MDA	1500-½ 393 (400-½) 1500-1 393 (400-1)
CIRCLING	1560-1 404 (500-1) 1620-1 464 (500-1) 1740-1½ 584 (600-1½) 2080-3 924 (1000-3)
MIRL Rwy 12-30 HIRL Rwy 6-24 REIL Rwy 12, 24 and 30	