

WAAS CH 61219 W01A	APP CRS 016°	Rwy Ldg 10302 TDZE 1314 Apt Elev 1333
--	------------------------	--

RNAV (GPS) Y RWY 1L

WICHITA DWIGHT D EISENHOWER NTL (ICT')

⚠ Inoperative table does not apply to LNAV Cat D. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). For inoperative ALSF-2, increase LNAV Cat C/D visibility to RVR 4500. DME/DME RNP-0.3 NA. Simultaneous approach authorized with ILS or LOC RWY 1R. LNAV procedure NA during simultaneous operations. Use of FD or AP providing RNAV track guidance required during simultaneous operations.

ALSF-2

MISSED APPROACH:
Climb to 3600 direct ACUBO and hold.

ATIS 125.15	WICHITA APP CON 126.7 353.5	WICHITA TOWER 118.2 257.8	GND CON 121.9 348.6
-----------------------	---------------------------------------	-------------------------------------	-------------------------------



ELEV 1333 D TDZE 1314

HIRL all Rwys
REIL Rwys 14 and 32
TDZ/CL Rwy 1L

4 NM Holding Pattern

CUTIK

JETUX

HAGEK 1.8 NM to RW01L

3600 ACUBO

GP 3.00° TCH 52

3600 ←196° →016°

3000

*1920

*0.8 NM to RW01L

*LNAV only.

6 NM

3.3 NM

1 NM

0.8 NM

CATEGORY	A	B	C	D
LPV DA	1514/18		200 (200-½)	
LNAV/VNAV DA	1615/24		301 (300-½)	
LNAV MDA	1620/24		306 (300-½)	
CIRCLING	1800-1	467 (500-1)	1980-1¾ 647 (700-1¾)	1980-2 647 (700-2)

1L

10302 X 150

6301 X 150

7302 X 150

TWR

1R

016°