



LOC I-ESF 111.5 Chan 52	APP CRS 270°	Rwy Ldg TDZE 92 Apt Elev 112	5998
---	------------------------	--	-------------

ILS or LOC/DME RWY 27

ESLR RGNL (E/SF')

RADAR or DME required.		MALSR	MISSED APPROACH: Climb to 1500 then climbing right turn to 3000 on heading 120° and on AEX VORTAC R-067 to LARTO/AEX 24.1 DME/RADAR and hold.
Circling Rwy 14, 32 NA at night. VDP NA with Alexandria Intl altimeter setting. When local altimeter not received, use Alexandria Intl altimeter setting and increase DA to 327 feet; increase all MDA to 40 feet and Circling visibility Cat D ¼ SM. For inop MALSR, increase S-LOC 27 Cat C/D visibility to 1 SM.			

ESF ASOS 119.425	MAKS APP CON 125.4 254.8	UNICOM 122.8 (CTAF) 0
----------------------------	------------------------------------	--



1500	3000	AEX R-067	LARTO AEX 24.1 RADAR	ESEME I-ESF 7 RADAR	Remain within 10 NM
*LOC only.					
GS 3.00° TCH 59					
CATEGORY	A	B	C	D	
S-ILS 27	292-½ 200 (200-½)				
S-LOC 27	440-½ 348 (400-½)		440-⅝ 348 (400-⅝)		
CIRCLING	600-1 488 (500-1)		740-1¾ 628 (700-1¾)		760-2 648 (700-2)