

WAAS CH 56313 W12A	APP CRS 124°	Rwy Ldg TDZE 8 Apt Elev 9
--	------------------------	---

RNAV (GPS) RWY 12

HOUMA-TERREBONNE (HUM)

RNP APCH - GPS.


▼

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C.
Rwy 12 helicopter visibility reduction below ¾ SM NA. Baro-VNAV and VDP NA when using MSY altimeter setting. When local altimeter setting not received, use MSY altimeter setting and increase LPV DA to 370 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 567 feet and all visibilities ¼ SM. Increase all MDAs 80 feet and LNAV visibility Cat B/C/D ¼ SM, and Circling visibility Cat B/C/D ¼ SM.

MISSED APPROACH:
Climb to 1800 direct HOVPU and hold.

ATIS 120.25	NEW ORLEANS APP CON 118.9 350.35	HOUMA TOWER ★ 125.3 (CTAF) 0 346.3	GND CON 123.875	UNICOM 122.95
-----------------------	--	--	---------------------------	-------------------------



4 NM Holding Pattern		1800 HOVPU	
NACIV		JOBUP	
6000 1800		1800	
GP 3.00° TCH 45		RW12	
6 NM		3.4 NM	
2 NM		2 NM	
CATEGORY	A	B	C
LPV DA	293-7 ⁸ / ₈	285 (300-7 ⁸ / ₈)	
LNAV/VNAV DA	490-1 ³ / ₈	482 (500-1 ³ / ₈)	
LNAV MDA	680-1	672 (700-1)	680-1 ⁷ / ₈ 672 (700-1 ⁷ / ₈)
CIRCLING	680-1	671 (700-1)	760-2 ¹ / ₄ 751 (800-2 ¹ / ₄) 760-2 ¹ / ₂ 751 (800-2 ¹ / ₂)

