

WAAS CH 93511 W02A	APP CRS 023°	Rwy Ldg 6007 TDZE 433 Apt Elev 433
--	------------------------	---

RNAV (GPS) RWY 2

JACKSON RGNL (MKL)

RNP APCH - GPS.

▼



▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C.
For inop ALS, increase visibility LNAV Cats A/B to 1 SM, and Cats C/D to 1 3⁄8 SM.

MALSR

MISSED APPROACH:
Climb to 3000 direct
GARTZ and hold.

ASOS 119.325	MEMPHIS CENTER 134.65 316.15	JACKSON TOWER ★ 127.15 (CTAF) 0 249.95	GND CON 120.9	UNICOM 122.95
------------------------	--	--	-------------------------	-------------------------



CATEGORY	A	B	C	D
LPV DA	772-3⁄4 339 (400-3⁄4)			
LNAV/VNAV DA	886-7⁄8 453 (500-7⁄8)			
LNAV MDA	900-3⁄4 467 (500-3⁄4)		900-1 467 (500-1)	
CIRCLING	900-1 467 (500-1)	920-1 487 (500-1)	960-1½ 527 (600-1½)	1080-2 647 (700-2)