

LOC I-DVS
111.9

APP CRS
357°

Rwy Ldg
TDZE **8501**
Apt Elev **790**

ILS or LOC RWY 35

GERALD R FORD INTL (G.R.R.)

DME required. DME or RADAR required for procedure entry.

⚠

HONSE fix minimums: for inop ALS, increase Cat C and D visibility to RVR 6000.
** RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 1300 then climbing left turn to 3000 on VIO VOR/DME R-353 to WALKS 13.7 DME and hold.

ATIS 118.725	GREAT LAKES APP CON★ 128.4 257.6	GRAND RAPIDS TOWER★ 135.65 (CTAF) 0 339.8	GND CON 121.8	UNICOM 122.95
------------------------	--	---	-------------------------	-------------------------

MISSED APCH FIX

LOCALIZER 111.9
I-DVS

ALTERNATE MISSED APCH FIX

HONSE INT VIO 2.9

CALDO OM/RADAR

VICTORY 115.95 VIO Chan 106(Y)

2500 to OM (6.4)

(IF/IAF) JUDD VIO 6.4

HOLD 5200 3000

MSA VIO 25 NM

ELEV 794 D TDZE 790

MIRL Rwy 8L-26R
REIL Rwys 8L, 17 and 26R
HIRL Rwys 8R-26L and 17-35

FAF to MAP 4.9 NM

Knots	60	90	120	150	180
Min:Sec	4:54	3:16	2:27	1:58	1:38

1300	3000	WALKS	VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 74).				One Minute Holding Pattern			
VIO R-353	VIO R-353	VIO R-353	VIO VOR/DME CALDO OM/RADAR	JUDD VIO 6.4	177°	5200				
*LOC only.	*VIO 3.8	HONSE INT VIO 2.9	2412	357°	2500	3000				
VIO 4.9	VIO 3.8	VIO 2.9	*1480	357°	2500	3000				
1.1 NM	0.9 NM	2.9 NM	6.4 NM							
CATEGORY	A	B	C	D						
S-ILS 35**	990/24				200 (200-½)					
S-LOC 35	1480/24	690 (700-½)	1480-1½	690 (700-1½)						
CIRCLING	1480-1	686 (700-1)	1480-2	686 (700-2)	1480-2¼	686 (700-2¼)				
HONSE MINIMUMS (ADF OR DME REQUIRED)										
S-LOC 35	1200/24	410 (500-½)	1200/40	410 (500-¾)						
CIRCLING	1260-1	466 (500-1)	1340-1½	546 (600-1½)	1360-2	566 (600-2)				

GRAND RAPIDS, MICHIGAN

Amdt 2B 30JAN20

42°53'N-85°31'W

GERALD R FORD INTL (G.R.R.)

ILS or LOC RWY 35