

WAAS CH 42726 W23A	APP CRS 234°	Rwy Ldg TDZE 443 Apt Elev 459
--	------------------------	---

RNAV (GPS) RWY 23

MOORE COUNTY (SOP)

RNP APCH.


▼

Baro-VNAV NA when using Sanford altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. When local altimeter setting not received, use Sanford altimeter setting and increase all DA 88 feet and all MDA 100 feet; increase LNAV Cats C/D visibility ³/₈ mile and Circling Cat C visibility ¹/₂ mile. Rwy 23 helicopter visibility reduction below ³/₄ SM NA.

MISSED APPROACH:

Climb to 2500 direct HEBNO and hold.

AWOS-3PT 127.575	FAYETTEVILLE APP CON 127.8 343.725	UNICOM 123.05(CTAF) 0
----------------------------	--	---------------------------------



ELEV 459 **D** TDZE 443

REIL Rwy 23 0

HIRL Rwy 5-23 0

2500 HEBNO				
VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 41).				
*LNAV only				
MOKSE 2.4 NM to RW23				
BUNEW 2100				
RW23				
*1240				
2.4 NM 2.7 NM 5 NM				
OWWEN 2500				
GP 3.00° TCH 54				
CATEGORY	A	B	C	D
LPV DA	693-1 250 (300-1)			
LNAV/VNAV DA	699-1 256 (300-1)			
LNAV MDA	780-1 337 (400-1)			
CIRCLING	880-1 421 (500-1)	920-1 461 (500-1)	1100-1 ³ / ₄ 641 (700-1 ³ / ₄)	1360-3 901 (1000-3)