

WAAS CH 69423 W28A	APP CRS 284°	Rwy Ldg TDZE 1189 Apt Elev 1191
--	------------------------	---

RNAV (GPS) RWY 28

KNOX COUNTY (4I3)

RNP APCH.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.

MISSED APPROACH: Climb to 3000 direct BONIF and hold.

AWOS-3PT
126.05

COLUMBUS APP CON
125.95 317.775

CLNC DEL
119.45

UNICOM
123.05 (CTAF) 0

MISSED APCH FIX

BONIF

104°

284°

4 NM

MSA RW 28 25 NM

3100

1273±

RW28

SLAPT 1.7 NM to RW28

(FAF) WEBUB

2700 284° (6.9)

(IF/IAF) PATIE

4 NM

HOLD 6000 2800

Procedure NA for arrival on APE VORTAC airway radials 055 CW 168.

APPLETON APE

3000 099° (13.5)

2800 NoPT 014° (9.8)

(IAF) TUCUG

2800 NoPT 305° (13.6)

(IAF) ROSCO

ELEV 1191

TDZE 1189

10

5504 X 100

28

284°

3000 BONIF

*LNAV only

SLAPT 1.7 NM to RW28

*1 NM to RW28

RW28

WEBUB 2700

PATIE

4 NM Holding Pattern

104° 6000 284° 2800

GP 3.00° TCH 40

1 NM

0.7

2.9 NM

6.9 NM

CATEGORY	A	B	C	D
LPV DA		1389-1	200 (200-1)	
LNAV/VNAV DA		1439-1	250 (300-1)	
LNAV MDA		1540-1	351 (400-1)	

MIRL Rwy 10-28 0

REIL Rwys 10 and 28 0

MOUNT VERNON, OHIO

Amtd 1D 07NOV19

40°20'N-82°32'W

KNOX COUNTY (4I3)

RNAV (GPS) RWY 28

EC-2, 06 AUG 2026 to 03 SEP 2026

EC-2, 06 AUG 2026 to 03 SEP 2026