



DETROIT DEP CON
118.95 284.0
ATIS
134.55
CINC DEL
121.6
GND CON
121.6
ANN ARBOR TOWER ★
120.3 (CTAF)




MALTB
2200



(40)
10000
2200
*2200
090°

BROKK

10000
2200
*2200



RNAV-1 DME/DME/IRU or GPS.
RADAR required.

TOP ALTITUDE:
ASSIGNED BY ATC

HHOWE FOUR DEPARTURE (RNAV)
(HHOWE4.HHOWE) 16MAY24

ANN ARBOR MUNI (ARB)
ANN ARBOR, MICHIGAN

NOTE: Turbojet departures at/above 10000, maintain 280K until advised by ATC.
NOTE: BROKK TRANSITION: For use by flights filed at or below FL270, or as assigned by ATC.

TAKEOFF MINIMUMS:
Rwy 6, 24: Standard.
Rwy 12, 30: NA - Environmental.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 6: Climb on heading 060° or as assigned by ATC, thence....
TAKEOFF RUNWAY 24: Climb on heading 240° or as assigned by ATC, thence....
....for RADAR vectors to cross MALTB at or above 2200, then on track 094° to HHOWE, then on (transition).
Maintain ATC assigned altitude, expect filed altitude 10 minutes after departure.

BROKK TRANSITION (HHOWE4.BROKK):
LINCON TRANSITION (HHOWE4.LINCON):

ANN ARBOR, MICHIGAN
ANN ARBOR MUNI (ARB)